



PYRO SHIELD, INC.

Insulation, Fabrication and Warehouse • FREE Local Delivery

www.PyroShield.com



PROTECT YOUR INVESTMENT
Pyro Shield Heat Barrier Solutions

PYRO SHIELD 2012 | ALL RIGHTS RESERVED

PS-2200 KEVLAR FIBERGLASS DATA SHEET

Applications

- Covers
- Sleeves
- Heat shields
- Curtains
- Tadpole seals



About the Fabric

Weave: Aramid fiber blend

Color: Yellow

Coating: None

Weight:

22 oz / y² +/- 10 % oz / yd²

Thickness:

0.08 in +/- 0.001 in

Temperature Resistance:

600°F

Count: 20 x 11

Tensile Strength:

WARP: 225 lbs / inch

FILL: 150 ends / inch

All statements are expressed opinion which we believe to be accurate, reliable, and presented without guarantee or responsibility on our part. The data presented above consists of typical properties and should not be used in preparing specifications. No warranties are expressed or implied and users should test this material thoroughly for their specific application.

(219) 661-8600 • Fax: (219) 661-8612
1171 E. Erie Court • Crown Point, IN 46307
FREE Local Delivery

General Questions
or Quotes Contact
sales@pyroshield.com

(281) 941-9054 • Fax: (281) 941-4437
1424 Sens Road Unit 3 • LaPorte, TX 77571
FREE Local Delivery in Houston Area